

#### **5730 LED HIGH EFFICACY TAPE LIGHT**





















ChipBrand

One BIN only for a CCT range

Lifetime


Certified

Certified

Warranty

Certified

Certified



#### Ra Available

#### IP Grade Available











#### **Features**

- High Light Efficacy
- Constant Voltage 24 VDC system
- Silicone extruded-IP68, Silicone tube encased-IP67, Silicone coated-IP65, indoor-IP22 available
- Epistar chips, LM80 tested
- Ra80+
- CE and RoHS certified
- 3 years warranty

#### BLUEVIEW ELEC-OPTIC TECH CO.,LTD



### **5730 LED HIGH EFFICACY TAPE LIGHT**

### **HIGH EFFICACY**

# **Specifications**

LED Type	SMD 5730	Dimmable	Yes (compatible with BV311 RF dimmer & BV Dimmer)
LED Q'ty/m	64pcs	IP grade	IP22 (IP65 &IP67&IP68)
Input Voltage	24V DC Constant Voltage	Installation	Heat-conductive adhesive tape (Heat sink is necessary)
Power	17.28±10%W/m	Working Temperature	-25~+60°C
Cutting length	125mm, 8 LEDs	Max run	5meters(Single Feed)
Strip Width	10mm	Certification	CE, RoHs
Viewing Angle	120°	Warranty	3 years

Order Code	CCT/ Color	Ra	Lumen/M <sup>2</sup>
CN-H5730-64-24-27K	2700K	80+	2165
CN-H5730-64-24-30K	3000K	80+	2195
CN-H5730-64-24-35K	3500K	80+	2220
CN-H5730-64-24-40K	4000K	80+	2225
CN-H5730-64-24-50K	5000K	80+	2260
CN-H5730-64-24-65K	6500K	80+	2282

Note: 1.Lumen output are measured according to PMS-80, with a tolerance of  $\pm$ -5%

- 2. Standard package: 5m/roll
- 3. The output power must be 24V. Neither higher nor less than 24V to avoid wattage affection on the striplight.

Order Code Model CN	Quality level  — H5730 —	LED Q'ty/M	Input voltage  — 24	CCT/Color
CN-IP22 CWS-IP65	H5730-3 yrs warranty		24V DC	view table above for options
CWT-IP67 CWE-IP68				



# **5730 LED HIGH EFFICACY TAPE LIGHT**


### **HIGH EFFICACY**



#### Unit:mm[in]



#### **Package**



#### Packing Info

Order Code	Net Weight / CTN	Gross Weight / CTN	Units / CTN	Carton Size
CN-H5730A-64-24	9.05(1±10%)	13.55(1±10%)	100 rolls	550*400*340mm