

















Ra Available

IP Grade Available













Features

- Super bright 2835 LEDs
- Epistar chips, LM-80 tested
- Ra90+/80+, with high R9 & R13 value
- Wide color temperature range, one bin only for one CCT
- Silicone extrusion (IP68), tube encased (IP67), silicone coated (IP65)
 & indoor (IP22) are available
- Cuttable every 3 LEDs for 12V, 6 LEDs for 24V
- 3M double sided tape for easy installation
- cULus Listed, 5 years warranty

BLUEVIEW ELEC-OPTIC TECH CO.,LTD



2835 Top LED Tape

Specifications

LED Type	SMD 2835	Dimmable	Yes (compatible with BV311 RF dimmer & BV Dimmer)
LED Q'ty/m	120pcs	IP grade	IP22 (IP65/68 available upon request)
Input Voltage	12V/24VDC Constant Voltage	Installation	3M [™] double sided tape(mounting clips for IP68)
Power	9.6W	Working Temperature	-40~+80 ℃
Cutting length	12V 25mm 3 LEDs 24V 50mm 6 LEDs	Max run	12V 1meter 24V 2.5meter
Strip Width	4mm	Certification	E354137 cULus Listed, CE, RoHs
Viewing Angle	120°	Warranty	5 years/ 3 years [©]

Order Code	CCT/ Color	CRI	Lumen/M ²
FN-2835A-120-12-25K	2425-2580K	80+, 90+	1160
FN-2835A-120-12-27K	2645-2800K	80+, 90+	1160
FN-2835A-120-12-30K	2850-3025K	80+, 90+	1160
FN-2835A-120-12-35K	3270-3545K	80+, 90+	1160
FN-2835A-120-12-42K	3840-4060K	80+, 90+	1200
FN-2835A-120-12-50K	4830-5095K	80+, 90+	1300
FN-2835A-120-12-55K	5400-5800K	80+, 90+	1300
FN-2835A-120-12-65K	6260-6680K	80+, 90+	1300
FN-2835A-120-12-90K	7836-9000K	80+	1300
FN-2835A-120-12-R	620-625nm	-	376
FN-2835A-120-12-G	520-525nm	-	1100
FN-2835A-120-12-B	465-470nm	_	288
FN-2835A-120-12-Y	594-596nm	_	336

Note:1. Contact Blueview for exact warranty period and policy

- 2. Lumen output are measured according to PMS-80, with a tolerance of \pm -5%
- 3. Standard package: 5m/roll
- 4. The output power must be 24V. Neither higher nor less than 24V to avoid wattage affection to the strip light.

Order Code

	Model	Quality level	LED Q'ty/M		Input voltage		CCT/Color
	MN		120]-[12	_	25K
	MN-IP22	2835A-5 yrs warranty			12-12V DC	Vİ	ew table above for options
N	/WS-IP65	2835B-3 yrs warranty			24-24V DC		

BLUEVIEW ELEC-OPTIC TECH CO.,LTD

Tel: +86-28-8148 0011 Fax: +86-28-8148 1258
Mail: sales@blueviewled.com Web.: www.blueviewled.com
Add: No.1000, Section 2, 2nd Konggang Road, Southwest
Aviation Industrial Development Zone, Chengdu, Sichuan, China.
Zip code: 610207

Specifications are subject to change without notice.


© Blueview™ 2016 – All rights reserved. Made in China.



2835 Top LED Tape

Dimension /

Unit:mm[in]




ھ

IP22


Package



Place the product neatly on the cardboard, fixed on the cardboard with the clear tape. Then layer and layer overlap, add a piece of cardboard on the top to protect product. Put products into the carton box and seal with the sealing tape.







Packing Info

	Product Code	Product Size	Qty (pcs)	Net Weight	Gross Weight
М	1N-2835A-120-4mm	5M*4mm	140	5.1 (1±10%)	10.1 (1±10%)

- 1. Put products 36 pcs(1M/pcs)flat on piece of cardboard. Then layer 36 layers overlap with a piece of cardboard on the top of each layer to protect the products. Use sealing tap to make all the layer as a block .Then put the block into the carton box.
- 2. Carton box size: 1100*185*185mm.

BLUEVIEW ELEC-OPTIC TECH CO.,LTD

Tel: +86-28-8148 0011 Fax: +86-28-8148 1258
Mail: sales@blueviewled.com Web.: www.blueviewled.com
Add: No.1000, Section 2, 2nd Konggang Road, Southwest
Aviation Industrial Development Zone, Chengdu, Sichuan, China.
Zip code: 610207

Specifications are subject to change without notice.

© Blueview™ 2016 – All rights reserved. Made in China.